

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: Compare To FUEL for LIFE (W) by Diesel ® F22075(Contains:Acetyl cedrene, Benzyl salicylate, alpha-Hexylcinnamaldehyde, alpha-Methyl-1,3-benzodioxole-5-propionaldehyde)

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Fragrances

1.3 Details of the supplier of the safety data sheet

Company name: Aromatic Fragrances International

Company address: 85 Wansley Drive SE
Cartersville, GA 30121
USA

Contact: Regulatory Affairs

E-Mail address: regulatory@afi-usa.com

Company phone: 770-334-3906

1.4 Emergency telephone number

Emergency phone: 770-334-3906

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Class and category of danger: Flammable Liquid, Hazard Category 4
Skin Corrosion / Irritation Category 3
Sensitization - Skin Category 1
Hazardous to the Aquatic Environment - Acute Hazard Category 1
Hazardous to the Aquatic Environment - Long-term Hazard Category 2
H227, Combustible liquid.
H316, Causes mild skin irritation.
H317, May cause an allergic skin reaction.
H400, Very toxic to aquatic life.
H411, Toxic to aquatic life with long lasting effects.

2.2 Label elements

Signal word: Warning

Hazard statements: H227, Combustible liquid.
H316, Causes mild skin irritation.
H317, May cause an allergic skin reaction.
H400, Very toxic to aquatic life.
H411, Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

Precautionary statements:

P210, Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P261, Avoid breathing vapour or dust.
P272, Contaminated work clothing should not be allowed out of the workplace.
P273, Avoid release to the environment.
P280, Wear protective gloves/eye protection/face protection.
P302/352, IF ON SKIN: Wash with plenty of soap and water.
P333/313, If skin irritation or rash occurs: Get medical advice/attention.
P363, Wash contaminated clothing before reuse.
P370/378, In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391, Collect spillage.
P403/235, Store in a well-ventilated place. Keep cool.
P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

Pictograms:



2.3 Other hazards

Other hazards: Hydrocarbon Concentration %: 0.0000%

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	%	GHS Classification
alpha-Hexylcinnamaldehyde	101-86-0	10-<20%	Acute Tox. 5-Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 2;H303-H316-H317-H400-H411
Ethylene brassylate	105-95-3	10-<20%	Aquatic Acute 2-Aquatic Chronic 3;H401-H412
1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran	1222-05-5	10-<20%	Skin Irrit. 3-Aquatic Acute 1-Aquatic Chronic 1;H316-H410
Methyl dihydrojasmonate	24851-98-7	5-<10%	Aquatic Acute 2;H401
2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol	63500-71-0	1-<5%	Eye Irrit. 2A;H319
Acetyl cedrene	32388-55-9	1-<5%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H303-H317-H410
beta-Ionone	14901-07-6	1-<5%	Acute Tox. 5-Aquatic Acute 2-Aquatic Chronic 2;H303-H411
alpha-Methyl-1,3-benzodioxole-5-propionaldehyde	1205-17-0	1-<5%	Acute Tox. 5-Skin Sens. 1B-Repr. 2-Aquatic Acute 2-Aquatic Chronic 2;H303-H317-H361-H411
Benzyl salicylate	118-58-1	1-<5%	Acute Tox. 5-Eye Irrit. 2B-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 3;H303-H317-H320-H401-H412

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

3,7-Dimethyl-1,6-nonadien-3-yl acetate	61931-80-4	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H315-H317-H319-H411
Isobutyl salicylate	87-19-4	0.1-<1%	Acute Tox. 4-Aquatic Acute 1-Aquatic Chronic 2;H302-H400-H411
3-(5,5,6-Trimethylbicyclo[2.2.1]hept-2-yl)cyclohexan-1-ol	3407-42-9	0.1-<1%	Repr. 2-Aquatic Acute 1-Aquatic Chronic 2;H361-H400-H411
d-Limonene	5989-27-5	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 3;H226-H304-H315-H317-H400-H412
2,2-Dimethyl-3-phenylpropanol	13351-61-6	0.1-<1%	Acute Tox. 4-Skin Irrit. 2-Eye Irrit. 2A-Aquatic Acute 3-Aquatic Chronic 3;H302-H315-H319-H412
Linalyl acetate	115-95-7	0.1-<1%	Flam. Liq. 4-Skin Irrit. 2-Eye Irrit. 2B-Skin Sens. 1B-Aquatic Acute 3;H227-H315-H317-H320-H402
Benzyl benzoate	120-51-4	0.1-<1%	Acute Tox. 4-Aquatic Acute 1-Aquatic Chronic 2;H302-H400-H411
alpha-Guaiene	3691-12-1	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2A-Asp. Tox 1;H304-H315-H319
Geraniol	106-24-1	0.1-<1%	Acute Tox. 5-Skin Irrit. 2-Eye Dam. 1-Skin Sens. 1-Aquatic Acute 3;H303-H315-H317-H318-H402
Coumarin	91-64-5	0.1-<1%	Acute Tox. 4-Skin Sens. 1B-Aquatic Acute 3;H302-H317-H402
Hexyl salicylate	6259-76-3	0.1-<1%	Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H316-H317-H410
beta-Caryophyllene	87-44-5	0.1-<1%	Skin Sens. 1B-Asp. Tox 1;H304-H317
cis-Jasmone	488-10-8	0.1-<1%	Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2B-Aquatic Acute 3;H303-H315-H320-H402

Substances with workplace exposure limits, not listed above:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.

Skin exposure: IF ON SKIN: Wash with plenty of soap and water.

Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes mild skin irritation.

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation. Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Free flowing liquid without sediment
Odour:	Characteristic
Odour threshold:	Not determined
pH:	Not determined
Melting point / freezing point:	Not determined
Initial boiling point / range:	Not determined
Flash point:	82 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Upper/lower flammability or explosive limits:	Product does not present an explosion hazard
Vapour pressure:	Not determined
Vapour density:	Not determined
Relative density:	Not determined
Solubility(ies):	Not determined
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not expected
Oxidising properties:	Not expected

9.2 Other information:

Flash Point (Fahrenheit):	180 °F
Calculated VOC:	3.69

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Acute Toxicity:	Based on available data the classification criteria are not met.
Acute Toxicity Oral	>5000
Acute Toxicity Dermal	Not Applicable
Acute Toxicity Inhalation	Not Available
Skin corrosion/irritation:	Skin Corrosion / Irritation Category 3
Serious eye damage/irritation:	Based on available data the classification criteria are not met.
Respiratory or skin sensitisation:	Sensitization - Skin Category 1
Germ cell mutagenicity:	Based on available data the classification criteria are not met.
Carcinogenicity:	Based on available data the classification criteria are not met.
Reproductive toxicity:	Based on available data the classification criteria are not met.
STOT-single exposure:	Based on available data the classification criteria are not met.
STOT-repeated exposure:	Based on available data the classification criteria are not met.
Aspiration hazard:	Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Ingredient	CAS	LD50/ATE Oral (mg/kg)	LD50/ATE Dermal (mg/kg)	LC50/ATE Inhalation	LC50 Route
Acetyl cedrene	32388-55-9	4500	Not available	Not available	Not available
Benzyl salicylate	118-58-1	2227	Not available	Not available	Not available
alpha-Hexylcinnamaldehyde	101-86-0	3100	Not available	Not available	Not available
alpha-Methyl-1,3-benzodioxole-5-propionaldehyde	1205-17-0	3562	Not available	Not available	Not available
beta-Ionone	14901-07-6	3940	Not available	Not available	Not available

Refer to Sections 2 and 3 for additional information.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

Section 12. Ecological information

12.1 Toxicity:

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran, Acetyl cedrene)	9	-	III
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran, Acetyl cedrene) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran, Acetyl cedrene)	9	-	III
ICAO TI	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran, Acetyl cedrene)	9	-	III

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

14.5 Environmental hazards: This is classified as an environmentally hazardous substance under the UN Model Regulations. This is classified as a Marine Pollutant under the IMDG Code.

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

Essential Oil Components:

Name	CAS	%
Patchouli oil	84238-39-1, 8014-09-3	1-<5%
Orange oil, sweet, terpenes	8028-48-6, 68647-72-3	0.1-<1%
Cedarwood oil, Atlas	92201-55-3, 8023-85-6	<0.1%
Balsam oil, Peru	8007-00-9	<0.1%
Guaiac wood oil	89958-10-1, 8016-23-7	<0.1%
Vetiver oil	84238-29-9, 8016-96-4	<0.1%
Calamus oil	84775-39-3, 8015-79-0	<0.1%

Components listed on California's Proposition 65:

Name	CAS	%
Myrcene	123-35-3	<0.1%

Naturally-Occuring Materials exempt from Prop65:

Name	CAS	%
Myrcene	123-35-3	

Components listed on California's SB312

Name	CAS	%
alpha-Hexylcinnamaldehyde	101-86-0	10-<20%
Benzyl salicylate	118-58-1	1-<5%
Di-(2-ethylhexyl) adipate	103-23-1	1-<5%
Benzyl benzoate	120-51-4	0.1-<1%
Geraniol	106-24-1	0.1-<1%
Coumarin	91-64-5	0.1-<1%
Eugenol	97-53-0	<0.1%

Additional formulation properties

Name	CAS	%
Vanillin	121-33-5	<0.1%
Ethyl vanillin	121-32-4	<0.1%

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

Section 16. Other information

Concentration % Limits: SCI 3=16.46% SS 1=5.01% EH A1=66.89% EH A2=6.27% EH A3=0.62677646% EH C2=13.93% EH C3=1.38% EH C4=44.95%

Total Fractional Values: SCI 3=6.08 SS 1=19.96 EH A1=1.49 EH A2=15.95 EH A3=159.55 EH C2=7.18 EH C3=72.42 EH C4=2.22

Key to revisions:

Not applicable

Key to abbreviations:

Abbreviation	Meaning
Acute Tox. 4	Acute Toxicity - Oral Category 4
Acute Tox. 5	Acute Toxicity - Oral Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H361	Suspected of damaging fertility or the unborn child (exposure route).
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Compare To FUEL for LIFE (W) by Diesel ® F22075

Version: 1

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P281	Use personal protective equipment as required.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308/313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
Repr. 2	Toxic to Reproduction Category 2
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1	Sensitization - Skin Category 1
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.