

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: EARTHEN OAK F23846(Contains:Benzyl benzoate, Hexyl salicylate, Musk ketone, alpha-iso-Methylionone)

Other identifiers: 1057396

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Fragrances

1.3 Details of the supplier of the safety data sheet

Company name: Aromatic Fragrances International

Company address: 85 Wansley Drive SE
Cartersville, GA 30121
USA

Contact: Regulatory Affairs

E-Mail address: regulatory@afi-usa.com

Company phone: 770-334-3906

1.4 Emergency telephone number

Emergency phone: 770-334-3906

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Class and category of danger: Acute Toxicity - Oral Category 5
Skin Corrosion / Irritation Category 3
Eye Damage / Irritation Category 2
Sensitization - Skin Category 1
Carcinogenicity Category 2
Hazardous to the Aquatic Environment - Acute Hazard Category 1
Hazardous to the Aquatic Environment - Long-term Hazard Category 1
H303, May be harmful if swallowed.
H316, Causes mild skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H351, Suspected of causing cancer (exposure route).
H410, Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Signal word: Warning

Hazard statements: H303, May be harmful if swallowed.
H316, Causes mild skin irritation.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H351, Suspected of causing cancer (exposure route).
H410, Very toxic to aquatic life with long lasting effects.

Precautionary statements:

P202, Do not handle until all safety precautions have been read and understood.
P261, Avoid breathing vapour or dust.
P264, Wash hands and other contacted skin thoroughly after handling.
P272, Contaminated work clothing should not be allowed out of the workplace.
P273, Avoid release to the environment.
P280, Wear protective gloves/eye protection/face protection.
P302/352, IF ON SKIN: Wash with plenty of soap and water.
P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308/313, IF exposed or concerned: Get medical advice/attention.
P312, Call a POISON CENTRE or doctor/physician if you feel unwell.
P333/313, If skin irritation or rash occurs: Get medical advice/attention.
P337/313, If eye irritation persists: Get medical advice/attention.
P363, Wash contaminated clothing before reuse.
P391, Collect spillage.
P405, Store locked up.
P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

Pictograms:



2.3 Other hazards

Other hazards: Hydrocarbon Concentration %: 0.0000%

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	%	GHS Classification
Hexyl salicylate	6259-76-3	20-<50%	Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H316-H317-H410
Benzyl benzoate	120-51-4	20-<50%	Acute Tox. 4-Aquatic Acute 1-Aquatic Chronic 2;H302-H400-H411
Vanillin	121-33-5	5-<10%	Acute Tox. 5-Acute Tox. 5-Eye Irrit. 2A-Aquatic Acute 3; H303-H313-H319-H402

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

alpha-iso-Methylionone	127-51-5	5-<10%	Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H316-H317-H411
Ethyl vanillin	121-32-4	1-<5%	Acute Tox. 5-Eye Irrit. 2B-Aquatic Acute 3;H303-H320-H402
2-Methyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol	28219-60-5	1-<5%	Eye Irrit. 2B-Aquatic Acute 2-Aquatic Chronic 2;H320-H411
Isolongifolene ketone	23787-90-8	1-<5%	Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H316-H317-H411
Coumarin	91-64-5	1-<5%	Acute Tox. 4-Skin Sens. 1B-Aquatic Acute 3;H302-H317-H402
2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol	63500-71-0	1-<5%	Eye Irrit. 2A;H319
Benzyl salicylate	118-58-1	1-<5%	Acute Tox. 5-Eye Irrit. 2B-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 3;H303-H317-H320-H401-H412
Ethyl maltol	4940-11-8	1-<5%	Acute Tox. 4-Aquatic Acute 2;H302-H401
Cedrol methyl ether	19870-74-7	1-<5%	Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H317-H410
Musk ketone	81-14-1	1-<5%	Carc. 2-Aquatic Acute 1-Aquatic Chronic 1;H351-H410
1-(2-tert.-Butyl cyclohexyloxy)-2-butanol	139504-68-0	1-<5%	Eye Irrit. 2B-Aquatic Acute 2-Aquatic Chronic 2;H320-H411
Linalyl acetate	115-95-7	0.1-<1%	Flam. Liq. 4-Skin Irrit. 2-Eye Irrit. 2B-Skin Sens. 1B-Aquatic Acute 3;H227-H315-H317-H320-H402
Eucalyptol	470-82-6	0.1-<1%	Flam. Liq. 3-Acute Tox. 5-Eye Irrit. 2B-Skin Sens. 1B-Aquatic Acute 3;H226-H303-H317-H320-H402
2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol	28219-61-6	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2B-Aquatic Acute 2-Aquatic Chronic 2;H315-H320-H411
4-tert-Butylcyclohexyl acetate	32210-23-4	0.1-<1%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 2;H303-H317-H401
Linalool	78-70-6	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3;H227-H303-H315-H317-H319-H402
2,2-Dimethyl-3-phenylpropanol	13351-61-6	0.1-<1%	Acute Tox. 4-Skin Irrit. 2-Eye Irrit. 2A-Aquatic Acute 3-Aquatic Chronic 3;H302-H315-H319-H412
Camphor	76-22-2	0.1-<1%	Flam. Sol. 2-Acute Tox. 4-Acute Tox. 4-Skin Irrit. 2-Eye Dam. 1-STOT SE 2-Aquatic Acute 2-Aquatic Chronic 2;H228-H302-H315-H318-H332-H371-H411
Acetyl cedrene	32388-55-9	0.1-<1%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H303-H317-H410
beta-Caryophyllene	87-44-5	0.1-<1%	Skin Sens. 1B-Asp. Tox 1;H304-H317
alpha-Cedrene	469-61-4	<0.1%	Skin Irrit. 2-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H304-H315-H410
beta-Cedrene	546-28-1	<0.1%	Skin Irrit. 2-Aquatic Acute 1-Aquatic Chronic 1;H315-H410

Substances with workplace exposure limits, not listed above:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin exposure: IF ON SKIN: Wash with plenty of soap and water.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May be harmful if swallowed.

Causes mild skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of causing cancer (exposure route).

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation. Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Free flowing liquid without sediment
Odour:	Characteristic
Odour threshold:	Not determined
pH:	Not determined
Melting point / freezing point:	Not determined
Initial boiling point / range:	Not determined
Flash point:	> 93 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Upper/lower flammability or explosive limits:	Product does not present an explosion hazard
Vapour pressure:	Not determined
Vapour density:	Not determined
Relative density:	1.0470 - 1.0770
Solubility(ies):	Not determined
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

Viscosity: Not determined

Explosive properties: Not expected

Oxidising properties: Not expected

9.2 Other information:

Flash Point (Fahrenheit): > 200 °F

Refractive Index @ 20C: 1.5263 - 1.5363

Color Range: 3 Very Pale Yellow - 1 Very Pale Yellow

Calculated VOC: 2.65

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Acute Toxicity: Acute Toxicity - Oral Category 5

Acute Toxicity Oral 2858

Acute Toxicity Dermal >5000

Acute Toxicity Inhalation Not Available

Skin corrosion/irritation: Skin Corrosion / Irritation Category 3

Serious eye damage/irritation: Eye Damage / Irritation Category 2

Respiratory or skin sensitisation: Sensitization - Skin Category 1

Germ cell mutagenicity: Based on available data the classification criteria are not met.

Carcinogenicity: Carcinogenicity Category 2

Reproductive toxicity: Based on available data the classification criteria are not met.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

STOT-single exposure: Based on available data the classification criteria are not met.

STOT-repeated exposure: Based on available data the classification criteria are not met.

Aspiration hazard: Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Ingredient	CAS	LD50/ATE Oral (mg/kg)	LD50/ATE Dermal (mg/kg)	LC50/ATE Inhalation	LC50 Route
Benzyl benzoate	120-51-4	1160	Not available	Not available	Not available
Benzyl salicylate	118-58-1	2227	Not available	Not available	Not available
Coumarin	91-64-5	500	Not available	Not available	Not available
Ethyl maltol	4940-11-8	1200	Not available	Not available	Not available
Ethyl vanillin	121-32-4	3000	Not available	Not available	Not available
Vanillin	121-33-5	3300	2600	Not available	Not available

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexyl salicylate, Benzyl benzoate)	9	-	III

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexyl salicylate, Benzyl benzoate) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexyl salicylate, Benzyl benzoate)	9	-	III
ICAO TI	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexyl salicylate, Benzyl benzoate)	9	-	III

14.5 Environmental hazards: This is classified as an environmentally hazardous substance under the UN Model Regulations. This is classified as a Marine Pollutant under the IMDG Code.

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

Essential Oil Components:

Name	CAS	%
Cedarwood oil, Virginian	85085-41-2, 8000-27-9	0.1-<1%
Gurjun balsam oil	8030-55-5	<0.1%
Orange peel, sweet, oil	8028-48-6, 8008-57-9	<0.1%

Components listed on California's Proposition 65:

Name	CAS	%
Myrcene	123-35-3	<0.1%

Naturally-Occuring Materials exempt from Prop65:

Name	CAS	%
Myrcene	123-35-3	

Components listed on California's SB312

Name	CAS	%
Benzyl benzoate	120-51-4	20-<50%
alpha-iso-Methylionone	127-51-5	5-<10%
Coumarin	91-64-5	1-<5%
Benzyl salicylate	118-58-1	1-<5%
Linalool	78-70-6	0.1-<1%

Additional formulation properties

Name	CAS	%
Vanillin	121-33-5	5-<10%
Ethyl vanillin	121-32-4	1-<5%

Section 16. Other information

Concentration % Limits:

SCI 3=15.10% EDI 2A=52.25% SS 1=3.19% CAR 2=83.33% EH A1=38.02% EH A2=3.72% EH A3=0.37137391% EH C1=71.11% EH C2=6.35% EH C3=0.63503998% EH C4=31.72%

Total Fractional Values:

SCI 3=6.62 EDI 2A=1.91 SS 1=31.39 CAR 2=1.20 EH A1=2.63 EH A2=26.88 EH A3=269.27 EH C1=1.41 EH C2=15.74 EH C3=157.47 EH C4=3.15

Key to revisions:

Concentration % Limits

SECTION 3: Composition/information on ingredients

Total Fractional Values

Key to abbreviations:

Abbreviation	Meaning
Acute Tox. 4	Acute Toxicity - Oral Category 4
Acute Tox. 4	Acute Toxicity - Inhalation Category 4

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

Acute Tox. 5	Acute Toxicity - Oral Category 5
Acute Tox. 5	Acute Toxicity - Dermal Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
Flam. Sol. 2	Flammable Solid, Hazard Category 2
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H228	Flammable solid.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer (exposure route).
H371	May cause damage to organs (organs, exposure route).
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: EARTHEN OAK F23846

Version: 2

P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe vapour or dust.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P281	Use personal protective equipment as required.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308/313	IF exposed or concerned: Get medical advice/attention.
P309/311	IF exposed or if you feel unwell: Call a POISON CENTRE or doctor/physician.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
STOT SE 2	Specific Target Organ Toxicity (Single Exposure) Category 2
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.